

- [54] TELEVISION PICTURE POSITIONING APPARATUS
- [75] Inventors: Thomas M. Gurley, Maple Shade; Robert S. Hopkins, Jr., Marlton; Wolf-Dieter Fischer, Turnersville, all of N.J.
- [73] Assignee: RCA Corporation, New York, N.Y.
- [21] Appl. No.: 862,178
- [22] Filed: Dec. 19, 1977
- [30] Foreign Application Priority Data
Mar. 21, 1977 [GB] United Kingdom 11905/77
- [51] Int. Cl.³ H04N 5/14; H04N 5/04
- [52] U.S. Cl. 358/160; 358/148
- [58] Field of Search 358/22, 148-150, 358/151-152, 160, 180-183; 340/724, 733

- [56] References Cited
- U.S. PATENT DOCUMENTS
- | | | | |
|------------|---------|--------------------|-----------|
| Re. 28,598 | 10/1975 | Baer et al. | 340/724 X |
| 3,740,743 | 6/1973 | Baron | 340/724 X |
| 3,758,712 | 9/1973 | Hudson | 358/183 |
| 3,781,849 | 12/1973 | Baron et al. | 340/733 X |
| 3,781,850 | 12/1973 | Gicca et al. | 340/733 X |
| 3,793,483 | 2/1974 | Bushnell | 358/148 |
| 3,835,245 | 9/1974 | Pieters | 340/733 X |
| 3,984,633 | 10/1976 | Rutt et al. | 358/183 X |
| 4,089,524 | 5/1978 | Hauck | 340/724 X |
| 4,099,205 | 7/1978 | Hatton et al. | 358/149 |
| 4,142,180 | 2/1979 | Burson | 340/724 X |

4,163,249 7/1979 Michael et al. 358/22 X
OTHER PUBLICATIONS

"A Digital Frame Store Synchronizer", Matley, Journal of SMPTE, Jun. 76, vol. 85, No. 6, pp. 385-387.
"Digital Frame Storage for Television Video", Pursell & Newby, Journal of SMPTE, Apr. 74, vol. 83, pp. 300-302.
"Television Frame Synchronizer", Kano et al., Journal of SMPTE Mar. 75, vol. 84, pp. 129-134.

Primary Examiner—James W. Moffitt
Assistant Examiner—Aristotelis M. Psitos
Attorney, Agent, or Firm—Eugene M. Whitacre; Paul J. Rasmussen; Robert L. Troike

[57] ABSTRACT

Apparatus which when implemented with a television video synchronizer permits the operator to position the synchronized picture at any desired location of the television raster including off the screen. A typical synchronizer includes a memory address generator for providing addresses to the memory for each active picture sample following sync timing and the video signals are stored in a predetermined nonvarying location in such a way that reading the stored video out of the memory reproduces the video signal. The positioning by the apparatus is achieved by modifying the storage addresses so that the relationship between sync timing and picture timing is changed.

8 Claims, 6 Drawing Figures

